

Washer Asy


Application

They are ideal for applications such as in hotels, houses, gardens, parks, plazas for the illumination of wall as wall washer light, as well as for ground washer light while recessed in the wall.



CE
IK07 IK06 IP67
SS316L cover

Recessed luminaire with asymmetric wall washer emission, equipped with thin flange and eyelid reflector, ensuring a high level visual comfort ! Silver reflector with high luminous efficiency as standard, black reflector with low UGR<18 as options. Asymmetrical beam 20° x 45° for 8W, and 20° x 50° for 15W, the wide washer light for the wall or ground is even and smooth, ideal for the places where should be designed with anti-glare and good washer lighting.



Washer Asy Mini -8W



Washer Asy Midi -15W





Silver reflector with high luminous efficiency as standard

black reflector with low UGR<18 as options



Aluminium cover version of 8W as wall light is available .



IP67 waterproof




Washer Asy Mini



CE RoHS IP67 IK06

3 Years Warranty


90°-cut-off angle.
Almost no light at this side.
Super visual comfort !
Light go up from bottom.




Parameter

General Data	
Item No.	EES8-Washer-Asym
Power	7.5 watts +10%
LED type	1PC 8V CREE CXA1304 COB LED
Luminous flux	430 lm±10% (Silver reflector)
CCT	2700K/3000K/4000K/5700K/6500K
CRI	80+
Beam angle	Anti-glare Asymmetrical 20° x 45 °
Dimension	Ø80*63 mm (Diameter x Height)
Cut out	Ø70mm
Net weight	0.6 kgs
Warranty	3 years as standard, 5 years as options
Certifications	CE, RoHS
Electrical Data	
Input voltage	DC24V
Insulation class	Class III
Cable	1PC 1M H05RN-F 2*1mm ² rubber cable
Driver	constant current driver DC24V input
Construction Data	
IP rating	IP67 Waterproof
IK rating	IK06
Housing	Aluminium
Protection finishing	Passivated in dark grey
Trim	SS 316L
Reflector	Silver colour as standard, black colour as options
Loading capacity	150 kgs
Cable Gland	PG7
Gasket	Silicone gasket
Accessories	
Mounting Sleeve	Aluminium tube in dark grey


Dimension



Light Distribution Curve (3000K, 20°x45°)



Lux distance Curve (3000K, 20°x45°)



Illumination Picture (20°x45°)




Washer Asy Midi



CE RoHS IP67 IK07

3 Years Warranty


90°-cut-off angle.
Almost no light at this side.
Super visual comfort !
Light go up from bottom.




Parameter

General Data	
Item No.	EES15-Washer-Asym
Power	15 watts +10%
LED type	1PC 15W CREE CMB1304F COB LED
Luminous flux	650 lm±10% (Silver reflector)
CCT	2700K/3000K/4000K/5700K/6500K
CRI	80+
Beam angle	Anti-glare Asymmetrical 20° x 45 °
Dimension	Ø100*82mm (Diameter x Height)
Cut out	Ø89mm
Net weight	1 kgs
Warranty	3 years as standard, 5 years as options
Certifications	CE, RoHS
Electrical Data	
Input voltage	DC24V
Insulation class	Class III
Cable	1PC 1M H05RN-F 2*1mm ² rubber cable
Driver	constant current driver DC24V input
Construction Data	
IP rating	IP67 Waterproof
IK rating	IK07
Housing	Aluminium
Protection finishing	Passivated in dark grey
Trim	SS 316L
Reflector	Silver colour as standard, black colour as options
Loading capacity	250 kgs
Cable Gland	PG7
Gasket	Silicone gasket
Accessories	
Mounting Sleeve	Aluminium tube in dark grey


Dimension




Light Distribution Curve (3000K, 20°x50°)



Lux distance Curve (3000K, 20°x50°)



Illumination Picture (20°x50°)



Light can reach a height of 5 meters

Recommend 1 meter between two items

Regular COB uplight

Washer Asy

6cm


Light starting from the bottom around 6cm away from the ground

Recommend 0.5m away from the wall

Recommend 0.3m away from the ground

Regular step light with a distance of 1m

Light can reach a distance of 5 meters



UWasher Asy 8W reach 5m away

Regular 3W step light reach 1m away

